

SENTRY® MODEL W02-1 PRESSURIZED WATER-TYPE FIRE EXTINGUISHER 2.5 GALLONS (9.5 LITERS)

Data/Specifications



FEATURES

- Meets or exceeds UL requirements
- Simple operation and maintenance
- Squeeze grip, positive on-off operation
- Brass chrome plated valve
- Waterproof stainless steel gauge
- Stainless steel shell
- Schrader valve for pressurization
- Easy service construction

DESCRIPTION

The ANSUL® Stainless Steel Water Extinguisher can be utilized in many Class A hazards such as office environments and industrial locations, as well as warehouse and oxidizing chemical storage areas. The unit features a stainless shell and chrome plated valve. The nameplate features easy to read step-by-step instructions for operating the extinguisher. The Schrader valve allows for easy recharge in the field. Use of fresh, clean water is recommended. Reference Manual F-83163.

SPECIFICATIONS

Model No.:	W02-1
UL Rating:	2-A
Capacity:	2.5 gallons (9.5 liters)
Extinguisher Height:	25.5 in. (64.8 cm)
Width:	9 in. (22.9 cm)
Depth:	7 in. (17.8 cm)
Range:	35 ft (10.7 meters)
Discharge Time:	Approximately 50 seconds
Bracket:	Wall mount
Temperature:	+40 °F to 120 °F (4.5 °C to 48.9 °C)



006492

ORDERING INFORMATION

Part No.	Description	Approximate Shipping Weight
430847	SENTRY® Model W02-1 Pressurized Water-Type Fire Extinguisher 2.5 Gallons (9.5 Liters)	9.0 lb (4.1 kg)

ANSUL and SENTRY are trademarks of Tyco Fire Suppression & Building Products or its affiliates.